



## Product information

3-way ball valve in "T" design. Reduced flow. Stainless steel.

Dimension range (DN)	15 - 65
PN	63
Temperature (°C)	-25 - 180
Main material	Stainless steel

### Area of use

3-way ball valve for distribution or mixing. T-shaped design.

### Tender text

#### **PSB.1 Ball valves**

## Measurements and weight

**Dimension range (DN):** 15 - 65

DN	A	B	C	Net weight (kg)
15	75	37	66	0.63
20	85	41	72	0.95
25	100	47	77	1.4
32	122	56	92	2.9
40	131	60	96	3.6
50	158	71	107	6.25
65	178	95	135	9

## Function and design

3-way valve with reduced flow in "T" design. Spindle with blow-out protection.

## Technical data

**Main material:** Stainless steel

**Main material code:** Acid resistant stainless steel AISI 316 (1.4408, CF8M)

**Included materials:** Stainless steel, Rubber, Other

**Included material code:** Stainless steel AISI 304 (1.4301), Acid resistant stainless steel AISI 316 (1.4401), Acid resistant stainless steel AISI 316 (1.4408, CF8M) , FPM/FKM (fluorine rubber), PTFE (polytetrafluoroethylene)

**Temperature (°C):** -25 - 180

**PN:** 63

**Connection:** Internal thread ISO 7/1 (BSPT, Kr)

**ETIM classification:** EC011343 - Ball valve

**BK04 code:** 20702 Ball valves

## Installation and maintenance

**Flowdirection:** Bi-directional

**Possible mounting position:** Vertical, Horizontal

The valve should be regularly exercised to avoid the accumulation of dirt that can lead to leakage.

Please feel free to contact us

We answer your questions by e-mail and telephone. No question is too small, no challenge is too big. You are always welcome at Armatec.

[info@armatec.se](mailto:info@armatec.se) | +46 31 89 01 00 | [www.armatec.se](http://www.armatec.se)

THE COMPANY'S MANAGEMENT SYSTEM  
IS CERTIFIED BY DNV  
ISO 9001 • ISO 14001