



Product information

Shut-off valve for heating, cooling, air, and gas systems. Can also be used for vacuum and lighter oils (such as diesel), see also section "Installation".

Dimension range (DN)	8 - 100
----------------------	---------

PN	25 - 40
----	---------

Temperature (°C)	-10 - 150
------------------	-----------

Material	Brass
----------	-------



Area of use

Shut-off valve for heating, cooling, air, and gas systems. Can also be used for vacuum and lighter oils (such as diesel), see also section "Installation". Silicone-free (the valve is free from silicone-based sealing or lubricating agents. No guarantee can be given that the article is free from silicone that may come from the environment, such as manual handling, transport, storage, etc.). PN40 for \leq DN50 (Max 40bar empty +95°C, max 25bar at +150°C) PN25 for \geq DN65 (Max 25bar empty +95°C, max 16bar at +150°C) Suitable for water 0°C to 150°C. Suitable for air -10°C to 150°C. Can be used down to -30°C in cooling systems with glycol-based media.

Tender text

PSB.1 Ball valves

Brass ball valve AT 3600, G... with full bore, internal thread and steel handle. Graphite packing.

Brass ball valve AT 3601, G... with full bore, internal thread, cast high spindle neck and steel handle. Graphite packing.

Brass ball valve AT 3602. With full bore, internal thread and lever. Graphite packing.

Quality assurance

AFS 2016:1, 8 paragraf

Product marking: Brand and DN.

Energy and environment declaration

Product Bvb: Avoided

Product BVB ID: 43123

SundaHus: C-

Reach notification obligation

Pos	Component	Material
-----	-----------	----------

Measurements and weight

Dimension range (DN): 8 - 100

Function and design

AT 3601 has a high spindle neck in DN 10-50. Suitable for installation where the valve needs to be over-insulated. AT 3600 and 3602 have a so-called "blow-out safe" spindle.

Technical data

Material: Brass

Material code: Brass (CuZn40Pb2) (CW617N) (2.0402)

Included materials: Brass, Steel, Other

Included material code: Brass (CuZn40Pb2) (CW617N) (2.0402), PTFE (polytetrafluoroethylene)

Temperature (°C): -10 - 150

PN: 25 - 40

Connection: Internal thread ISO 228-1 (G, BSPP)

ETIM classification: EC011343 - Ball valve

BK04 code: 20702 Ball valves

Installation and maintenance

Flowdirection: Bi-directional

Possible mounting position: Vertical, Horizontal

"All valves have internal pipe threads. Tightening of the packing may be necessary for air and gas systems when the test pressure exceeds 6 bar. The valve should be operated regularly to avoid the accumulation of dirt that can lead to leakage."

Please feel free to contact us

We answer your questions by e-mail and telephone. No question is too small, no challenge is too big. You are always welcome at Armatec.

info@armatec.se | +46 31 89 01 00 | www.armatec.se

THE COMPANY'S MANAGEMENT SYSTEM
IS CERTIFIED BY DNV
ISO 9001 • ISO 14001