

Product information

Check valve type EA in lead-free brass for liquid category 1-2 according to SS-EN 1717.

Dimension range (DN)	15 - 50
PN	10
Temperature (°C)	0 - 90
Material	Brass, Stainless steel, Plastic, Other



Tender text

PSE.31 Check valves in liquid systems

Quality assurance

Fluid category 2, SS-EN 1717


Energy and environment declaration

Product Bvb: Accepted

Product BVB ID: 115332

SundaHus: A

Pos	Component	Material
1		Brass (CuZn21Si3P) (CW724R)
2		Brass (CuZn35Pb1,5AlAs) (CW625N)
3		PTFE (polytetrafluoroethylene)
4		Plastic
5		Acid resistant stainless steel 316 (1.4401)



Measurements and weight

Dimension range (DN): 15 - 50

DN	15	20	25	32	40	50
A	70	70	80	90	103	120
B	26	31.5	39.5	49.5	54.4	68
Net weight (kg)	0.182	0.211	0.376	0.612	0.827	1.262

Technical data

Flowdirection: Uni-directional

Material: Brass, Stainless steel, Plastic, Other

Material code: Acid resistant stainless steel 316 (1.4401), Brass (CuZn21Si3P) (CW724R), Brass (CuZn35Pb1,5AlAs) (CW625N), PTFE (polytetrafluoroethylene)

Temperature (°C): 0 - 90

PN: 10

Connection: Internal thread ISO 228-1 (G, BSPP)

Possible mounting position: Horizontal

ETIM classification: EC011469 - Check valve

BK04 code: 20711 Non-return valves

Product information

We answer your questions by e-mail and telephone. No question is too small, no challenge is too big. You are always welcome at Armatec.

info@armatec.se | +46 31 89 01 00 | www.armatec.com

THE COMPANY'S MANAGEMENT SYSTEM
IS CERTIFIED BY DNV
ISO 9001 • ISO 14001