


HANDWHEEL	$\phi$ A	B	C	$\phi$ d	$\phi$ e	D
PS 100-12	100 [4.00]	35 [1.38]	5 [0.20]	12 [0.47]	4.1 [0.16]	16 [0.63]
PS 125-12	125 [5.00]	34 [1.34]	5 [0.20]	12 [0.47]	4.1 [0.16]	18 [0.71]
		48 [1.89]	10 [0.39]	15 [0.59]	5.1 [0.20]	18 [0.71]
PS 160-12	160 [6.50]	48 [1.89]	10 [0.39]	12 [0.47]	4.1 [0.16]	22 [0.87]
PS 160-15		49 [1.93]	10 [0.39]	15 [0.59]	5.1 [0.20]	22 [0.87]
PS 200-12	200 [8.00]	51 [2.01]	10 [0.39]	12 [0.47]	4.1 [0.16]	24 [0.94]
PS 200-15		52 [2.05]	10 [0.39]	15 [0.59]	5.1 [0.20]	24 [0.94]
PS 200-20		63 [2.48]	10 [0.39]	20 [0.79]	6.1 [0.24]	24 [0.94]
PS 250-12	250 [10.00]	63 [2.48]	10 [0.39]	12 [0.47]	4.1 [0.16]	31 [1.22]
PS 250-15		63 [2.48]	10 [0.39]	15 [0.59]	5.1 [0.20]	31 [1.22]
PS 250-20		70 [2.76]	10 [0.39]	20 [0.79]	6.1 [0.24]	31 [1.22]

**rotork-gears**

Nijverheidstraat 25  
7581 XJ Lasser  
The Netherlands

# HANDWHEELS TYPE PS

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : N.M.

Date : 09-01-07

Dwg Nr.: PS00-001

Rev.: 00

Contents Subject to change without notice.