



AT BRAZING OF PIPES, WRAP THE SWITCH BODY WITH WET CLOTH AND KEEP THE TEMPERATURE OF SWITCH BODY UNDER 100°C

★CONFIRMATION OF DESIGN VALIDITY  
 We manufacture the product based on the specifications described in this drawing. Please check the safety and validity in the product design in consideration that the product is conformed to the system or not when using.

JUN 19, '04	△	INK STAMPING->LABEL
DATE	SIGN	CHANGE CONTENT

OPERATING PRESS. CHARACTERISTICS.	OPERATING PRESS. SETTING		UNIT: bar		DIFFERENTIAL	
	OFF	O	N			
	22 ± 1	18 ± 1	—			
ELECTRICAL RATINGS	RATED VOLTAGE (V)		PF	A	C	DC
	RATED AMPS. (A)		Cos φ	125	250	12
	NON-INDUCTIVE AMPS.		1	1~6	1~4	1~4
	INDUCTIVE AMPS.	FULL LOAD AMPS.	0.75	1~6	1~4	—
STARTING AMPS.		0.45	1~24	1~16	—	
TYPE OF CONTACT						
CONTACT RESISTANCE	LESS THAN 200 m Ω					
INSULATION RESISTANCE	NOT LESS THAN 100 M Ω AT DC 500V MEGGER					
DIELECTRIC STRENGTH	WITHSTAND 1500V AC FOR ONE MINUTE					
MAX. PRESSURE	35 bar					
AIR TIGHT PRESS.	40 bar					
TEST PRESS.	50 bar					
MAX. ALLOW. TEMP.	-30 ~ 100 °C (But no freeze)					
DURABILITY	100,000 TIMES					
Checked by	Date	Name				
T. T.	MAR. 26 2003	TYPE CB PRESSURE SWITCH				
Designed by	Scale	Catalog Number	Drawing Number			
	1:1	ACB-JB206	N-CB-22298-1			
Drawn by	Code No. :061F 8195					
K. H.						