


Contact  
MOLEX 5556T  
Housing  
MOLEX 5557-02R

HEAT PROOF ELECTRIC VINYL WIRE  
UL1015, AWG18, 105°C (RED)

LABEL



φ 22.6



AT BRAZING OF PIPES, WRAP THE SWITCH BODY WITH WET CLOTH AND KEEP THE TEMPERATURE OF SWITCH BODY UNDER 100°C



OPERATING PRESS. SETTING	UNIT: bar		DIFFERENTIAL
	OFF	O N	
ELECTRICAL RATINGS	29 ± 1 27 ± 1	21 ± 1.5 19 ± 1	—
	RATED VOLTAGE (V)		D C
RATED AMPS. (A)		30	
INDUCTIVE AMPS.		0.001~0.075	

TYPE OF CONTACT	SINGLE POLE SINGLE THROW  PRESS. RISING
CONTACT RESISTANCE	LESS THAN 200 mΩ
INSULATION RESISTANCE	NOT LESS THAN 100 MΩ AT DC 500V MEGGER
DIELECTRIC STRENGTH	WITHSTAND 1500V AC FOR ONE MINUTE
MAX. PRESSURE	45 bar
AIR TIGHT PRESS.	45 bar
TEST PRESS.	50 bar
MAX. ALLOW. TEMP.	AMBIENT TEMP. -30 ~ 85°C (But no freeze) FLUID TEMP. -54 ~ 135°C
DURABILITY	100,000 TIMES
TÜV APPROVED	EN 12263 DIN 32733(DWK 4B 04102)

Checked by	Date	Name	TYPE CB PRESSURE SWITCH
H. S.	OCT. 31 2005		
Designed by	Scale	Catalog Number	Drawing Number
M. F.	1:1	ACB-4UB43W	N-CB-22716-1
Drawn by	Code No. :061F 8547		
M. Y.			

★CONFIRMATION OF DESIGN VALIDITY

We manufacture the product based on the specifications described in this drawing. Please check the safety and validity in the product design in consideration that the product is conformed to the system or not when using.

MAY. 13. 2006	1	REV. PRESS. SETTING
DATE	SIGN	CHANGE CONTENT

