

# STFT

Modello / Type / Modèle / Modell			STFT	12118	14121	12218	16124	14221	18127	16224	12239	18227	14245
Capacità Puissance	Rating Leistung	* ΔT 15 K	W	470	665	745	925	1000	1235	1385	1565	1935	2085
Port. aria rich. Débit air néc.	Req. air quant. Notw. Luftmenge		m³/h	255	330	220	450	290	650	390	440	570	580
Vent. nec. Vent. néc.	Fans req. Anz. Vent.		n° x Ø mm	1x170	1x200	1x170	1x230	1x200	1x254	1x230	2x170	1x254	2x200
Superficie Surface	Surface Oberfläche		m²	0,55	0,75	1,1	1	1,5	1,25	2	2,35	2,5	3,2
Volume interno Volume interne	Internal volume Rohrinhalt		dm³	0,13	0,18	0,26	0,25	0,36	0,3	0,5	0,56	0,6	0,75
Dimensioni Dimensions Dimensions Abmessungen		A	mm	185	215	185	245	215	275	245	395	275	455
		B	mm	184	214	184	244	214	274	244	184	274	214
		C	mm	30	30	60	30	60	30	60	60	60	60
Att. / Conn. / Racc. / Anchl.			Ø mm	8	8	8	8	8	8	8	8	8	8
Peso / Weight / Poids / Gewicht			kg	0,88	1,19	1,77	1,54	2,38	1,93	3,07	3,6	3,86	4,7

# CF

Convogliatore di plastica / Plastic fan shroud / Diffuseur en plastique / Kunststoff Einlaufring

Modello / Type / Modèle / Modell	CF	CF18	CF21	CF18	CF24	CF21	CF27	CF24	2xCF18	CF27	2xCF21
	Ø mm	178	206	178	236	206	260	236	178	260	206

20233	16251	18257	—	—	—
2730	2770	3670	—	—	—
900	780	1140	—	—	—
1x275	2x230	2x254	—	—	—
3,5	4,4	5,5	—	—	—
0,78	0,97	1,22	—	—	—
335	515	575	—	—	—
304	244	274	—	—	—
60	60	60	—	—	—
8	8	8	—	—	—
5,2	6,3	7,7	—	—	—
CF33	2xCF24	2xCF27	—	—	—
282	236	260	—	—	—

