

HYGIENE ECO

Low-temperature panel radiator made from high-quality steel, with serial flow technology (water flows first through the front panel). This results in high energy efficiency, maximum radiation (even in low-temperature heating systems), faster heating rate and less waste of energy.

Product:	low-temperature valve radiator specifically developed for environments where hygiene and safety are all-important, with serial flow technology, both a centre and lateral bottom connections and a preset valve insert, which can be fitted on the left or right side of the radiator
Finishing:	without upper grille or side panels and without convection fins
Pre-installed:	preset Heimeier 4368 or 4369 valve insert, ECO air vent and blind plugs
Valve insert:	<p>The integrated adjustable valve insert (without thermostatic head) is factory-fit on the right side of the radiator, CEN certified, tested in accordance with EN215 and compatible with thermostatic heads M30 x 1,5 mm. For types 20 – 30 the valve insert can also be fitted on the left side of the radiator, a left version for a type 10 radiator is available on request.</p> <p>The thermostatic valve insert is factory-set in relation to the size of the radiator.</p> <p>This presetting ensures optimum throughput in the radiator. Factory setting for two-pipe systems, also suitable for one-pipe systems (as long as the valve insert is adjusted to position 8).</p>
Also supplied:	assembly instructions
Connections:	2 x ¾" male Eurocone centre connection and 2 x ½" female lateral bottom connection
Lugs:	2 pairs of mounting lugs up to 1.600 mm and 3 pairs from 1.800 mm
Packaging:	Every radiator is sturdily packaged in high-quality cardboard and wrapped in plastic. The radiator's characteristics are shown on the label: type – height – length.
Warranty:	10 years, as long as the installation instructions have been followed and Stelrad's warranty conditions have been met.
Paint process:	All radiators are degreased, phosphated, cataphoretically primed and powder-coated in Stelrad white 9016 as standard.
Colours:	Stelrad white 9016 + 35 different Stelrad colours and about 200 RAL-colours are possible
Heat cost allocator:	Suitable for heat cost allocators, both electronic and according to the evaporation principle (covered by the norm of EN834 & EN835).
Max. operating pressure:	10 bar (tested to 13 bar)
Max. operating temperature:	110 °C
Conformity:	in accordance with EN442
Quality assurance:	Hygiene
Types:	10 20 30
Heights:	300 400 500 600 700 900 mm
Lengths:	400 – 3.000 mm
Depths:	47 77 158 mm