



Product information

3-way ball valve in "T" design. Reduced flow. Stainless steel.

Dimension range (DN)	15 - 65
PN	63
Temperature (°C)	-25 - 180
Main material	Stainless steel

Area of use

3-way ball valve for distribution or mixing. T-shaped design.

Tender text

PSB.1 Ball valves

Measurements and weight

Dimension range (DN): 15 - 65

DN	A	B	C
15	75	37	66
20	85	41	72
25	100	47	77
32	122	56	92
40	131	60	96
50	158	71	107
65	178	95	135

Function and design

3-way valve with reduced flow in "T" design. Spindle with blow-out protection.

Technical data

Main material: Stainless steel

Main material code: Acid resistant stainless steel 316 (1.4408, CF8M)

Included materials: Stainless steel, Rubber, Other

Included material code: Stainless steel 304 (1.4301), Acid resistant stainless steel 316 (1.4401), Acid resistant stainless steel 316 (1.4408, CF8M) , FPM/FKM (fluorine rubber), PTFE (polytetrafluoroethylene)

Temperature (°C): -25 - 180

PN: 63

Connection: Internal thread ISO 7/1 (BSPT, Kr)

ETIM classification: EC011343 - Ball valve

BK04 code: 20702 Ball valves

Installation and maintenance

Flowdirection: Bi-directional

Possible mounting position: Vertical, Horizontal

The valve should be regularly exercised to avoid the accumulation of dirt that can lead to leakage.

Please feel free to contact us

We answer your questions by e-mail and telephone. No question is too small, no challenge is too big. You are always welcome at Armatec.

info@armatec.se | +46 31 89 01 00 | www.armatec.se

THE COMPANY'S MANAGEMENT SYSTEM
IS CERTIFIED BY DNV
ISO 9001 • ISO 14001