



• SPECIFICATIONS

OPENING POINT MPa {kgf/cm ² }	RANGE MPa {kgf/cm ² }		PORT SIZE (mm)	MAX. DISCHARGE $\Delta P=0.05\text{MPa}$ {0.5kgf/cm ² } (l/min)	MAX. FLUID TEMPERATURE (°C)	MAX. WORKING PRESSURE MPa {kgf/cm ² }		AIRTIGHT (WATERTIGHT) TEST PRESSURE MPa {kgf/cm ² }		WATER TEST PRESSURE MPa {kgf/cm ² }
	MIN.	MAX.				BODY	BELLOWS CAP	BODY	BELLOWS CAP	
0.74 { 7.5 }	0.59 { 6.0 }	1.77 {18.0 }	12	15	60	0.98 {10.0 }	1.96 {20.0 }	0.98 {10.0 }	2.35 {24.0 }	1.72 {17.5 }
								(WATER)	(AIR)	

NOTE

WE MANUFACTURE THE PRODUCT BASED ON THE SPECIFICATIONS DESCRIBED IN THIS DRAWING. PLEASE CHECK THE SAFETY AND VALIDITY IN THE PRODUCT DESIGN IN CONSIDERATION THAT THE PRODUCT IS CONFORMED TO THE SYSTEM OR NOT WHEN USING.

Approved by	Date JAN. 30 1992	Name PRESSURE ACTUATED WATER REGULATING VALVE	
Designed by	Scale 1:1	Catalog Number AWR-1203GLW	Drawing Number N-WR-21007-1
Drawn by	SAGINOMIYA SEISAKUSHO, INC.		

MAR. 20. 1998 REVISION Asami