

Compressor


LPHX

KPH 90554/90567/10054/
11055

Capacity 55-95 m ³ /h	Pressure range 0,2-1,2 bar	Material Cast iron & Stainless steel
--	--------------------------------------	--

Description

A one stage liquid ring compressor with a simple robust design. With a free shaft end all options of shaft coupling, motor and DIN seals are available to adapt the pump to your industry.



AT 6300

Range application

Evacuation and pumping of dry gases and saturated steam, and combinations of these, from a lower pressure to a higher pressure.

Typical industries are chemical, pharmaceutical, food, plastic and rubber industry.

Vacuum is used for distillation, drying, degassing, filling and boiling.

Design

The pump works according to the liquid ring principle. Fluid pumps are in some regards related with displacement pumps since the pump wheel is eccentrically located in the round pump body. When the wheel is rotating a fluid ring is created along the pump body's inner wall. In the cells (the space between the pump body's wings) inside the fluid ring rising part volumes (intake) and then decreasing volumes (outlet) will be created under one rotation. Because of the intensive contact between the gas that is transported and the operating fluid, there is only a very little increase of temperature of the gas that is transported, so that it can be described as an isothermal compression. The fluid ring compression is used especially with high intake pressure, and has a double acting construction. The pump body makes intake and compression possible two times per rotation.

Material combinations

Pos	02	42
Casing	0.6025 Cast iron	1.4408 Acid-proof steel
Central body	1.0038 Steel	1.4571 Acid-proof steel
Guide disc	0.6025 Cast iron	1.4408 Acid-proof steel
Shaft	1.0503 Steel	1.0503 Steel
Impeller	1.0570 Steel	1.4571 Acid-proof steel